



SOLAR SOLENTURK

EKIP Ins. Ener. Dis. Tic. San. Ltd. Sti.

Fevzi Cakmak Mah., Medcezir Cad., Konya Ticaret Merkezi, No: 8 /

B-13, Karatay, Konya, TÜRKİYE

+90 - 332 - 320 - 5566

info@solenturk.com

www.solenturk.com



ST Series Solar Flood Light

Model	Product Pictures	Description Main Parameters
STR ST-60W		1. Chip: SanAn SMD7530 2. Wattage: 60W 3. Input: DC5V 4. Luminous: 515LM 5. Height of Installation: 3-5m 6. Charging time: 5-8 hours 7. Capacity: 3.2V/6000mA 8. Solar Panel: 5V/12W 9. Size Light: Die Casting Aluminium 215.2*170.2*60mm 10. Size Panel: 350*235*17 Polycrystal
STR ST-100W		1. Chip: SanAn SMD7530 2. Wattage: 100W 3. Input: DC5V 4. Luminous: 772LM 5. Height of Installation: 3-5m 6. Charging time: 5-8 hours 7. Capacity: 3.2V/12000mA 8. Solar Panel: 5V/15W 9. Size Light: Die Casting Aluminium 260.2*202.2*65mm 10. Size Panel: 350*290*17 Polycrystal
STR ST-200W		1. Chip: SanAn SMD7530 2. Wattage: 200W 3. Input: DC5V 4. Luminous: 1158LM 5. Height of Installation: 3-5m 6. Charging time: 5-8 hours 7. Capacity: 3.2V/18000mA 8. Solar Panel: 5V/25W 9. Size Light: Die Casting Aluminium 305.1*240.1*69mm 10. Size Panel: 450*350*17 Polycrystal
STR ST-300W		1. Chip: SanAn SMD7530 2. Wattage: 300W 3. Input: DC5V 4. Luminous: 1630LM 5. Height of Installation: 3-5m 6. Charging time: 5-8 hours 7. Capacity: 3.2V/24000mA 8. Solar Panel: 5V/35W 9. Size Light: Die Casting Aluminium 340.2*270.2*78mm 10. Size Panel: 580*350*25 Polycrystal
STR ST-400W		1. Chip: SanAn SMD7530 2. Wattage: 400W 3. Input: DC5V 4. Luminous: 2060LM 5. Height of Installation: 3-5m 6. Charging time: 5-8 hours 7. Capacity: 3.2V/30000mA 8. Solar Panel: 5V/40W 9. Size Light: Die Casting Aluminium 385.2*303.2*82mm 10. Size Panel: 630*350*25 Polycrystal
STR ST-500W		1. Chip: SanAn SMD7530 2. Wattage: 500W 3. Input: DC5V 4. Luminous: 2574LM 5. Height of Installation: 4-6m 6. Charging time: 5-8 hours 7. Capacity: 3.2V/48000mA 8. Solar Panel: 5V/50W 9. Size Light: Die Casting Aluminium 385.2*303.2*82mm 10. Size Panel: 670*445*25 Polycrystal

All Specifications:

1. Color Temp: 3000K/4000K/6500K

2. Detection Angle: 110°

3. Waterproof Grade: IP65

4. Material: ADC#12 Aluminium




5. Charge&Discharge: About 1000-1300 times

6. Battery: Replaceable

7. Cable: 5 meters

8. Weather Durability: 3 days

9. Remark: the sunlight on the panel that affects the charging is subject to the local weather, place and direction of the installation



PRODUCT PICTURES



No	Model	Pcs/Ctns	Color Box	GW/color box	Dimension L / W / H	G.W(kg)	Total G.W kg	Volume m ³ Ctn	20GP	40GP
1	ST 60w	7	22*18*6.6	2.05	42 / 37.5 / 27	12.6	14.3	0.04	4609	9218
2	ST 100w	5	26.5*21.3*7.1	2.82	36.5 / 31.5 / 38	12.5	14.1	0.04	3204	6409
3	ST 200w	6	31*24.6*7.5	3.82	47.5 / 43 / 38.5	20.1	22.9	0.08	2136	4273
4	ST 300w	4	34.5*27.8*8.4	5.12	60 / 30 / 38	18.2	20.45	0.07	1637	3275
5	ST 400w	4	39*31*8.8	5.84	65 / 31 / 41	20.8	23.35	0.08	1356	2711
6	ST 500w	2	39*31*8.8	7.35	69 / 17 / 47	13	14.7	0.06	1016	2032

REMARKS & WARRANTY

1. Price Term: EXW Shenzhen, China
 2. Payment Term: Trial order (less than 10pcs) T/T 100%, normal order T/T, 40% deposit before production, balance 60% paid before shipment.
 3. The price validity is within 15 days.
 4. Production Time: Around 25 working days after deposit transferred into the bank account.
 5. This price does not include freight, insurance, poles, installation fee and taxes.
1. This warranty does not cover damage or malfunction due to abuse, misuse, incorrect installation, or accidents resulting from the BUYER.
 2. The warranty for the battery will be void if not installed within 6 months after delivery.
 3. 2 years for the whole light.